Mr./Mrs./Ms.:						Model:							Reg. No.:								
Invoice/Job No.:					Odometer Reading:							V.I.N.:									
Service type:	0	Α	0	В	0	Α	0	В	0	Α	0	В	0	Α	0	В	0	Α	0	В	
Months:	6 7.5	12 15	18	24	30 37.5	36 45	42 52.5	48 60	54 67.5	60 75	66 82.5	72 90	78 97.5	84 105	90 112 5	96 120	102	108	114	120 150	



## DISCOVERY 3 (ALL MODELS REST OF WORLD)

Adjust/Lubricate/Replace - Labour cost included in scheduled time except items marked \*
Check - After the checking procedure, cleaning, adjusting, repairing or replacing is subject to extra labour and material cost.

neck	c - After	the checking procedure, cleaning, adjusting, repairing or replacing is subject to extra labour and mate	erial cos	st.		MAINTENANCE CHECK SHEET
	0	OIL SERVICE		Α	В	MAIN SERVICE (UNDER VEHICLE)
١.		Renew engine oil and filter (Every 6 months / 7,500 mile)	34.			Renew engine oil and filter
,		Check battery condition and check/top up battery electrolyte level (Every 6	35.		150k	Renew manual gearbox oil (Every 10 years)
•		months / 7,500 mile) - MENA markets only	36.		150k	Renew automatic transmission oil and filter (Every 10 years)
	Α	B MAIN SERVICE (VEHICLE INTERIOR)	37.	75k	150k	Renew transfer box oil, replace drain and fill plug washers
		Check condition and security of seats and seatbelts	38.		<u>                                   </u>	Renew front and rear axle oil (Every 10 years)
		Check operation of all lamps, horns and warning indicators	39. 40.	/5k	150k	Renew locking differential oil
		Check operation of front/rear wipers and washers and condition of wiper	40. 41.			Check for free play in all suspension and body mounting rubbers Check condition of all suspension, driveshafts and steering boots and gaiters
٠.		blades	42.		ıH	Replace all flexible brake hoses ( <i>Every 6 years</i> )*
		Select the LOW range gears and drive the vehicle 3 to 4 vehicle lengths then			' <u></u>	Check visually brake servo hose, brake, fuel, PAS and clutch pipes, unions
		re-select HIGH range gears	43.			and electrical harnesses for chafing, leaks and corrosion
		Replace pollen filter	44.			Adjust the electric park brake shoes
		MAIN SERVICE (VEHICLE EXTERIOR)	45.			Check for fluid leaks
		Annual corrosion/cosmetic inspection - Using annual corrosion inspection	46.			Check exhaust system for leaks, security and damage
		sheet	47.			Check steering rod ball joint fixings and condition of ball joints and dust covers
,		Check tyre pressures, condition and tread depth.	48.			Check torque of tie rod end nuts - M12 tie rod end nuts only - 76 Nm
			49.			If fault lamp(s) are illuminated, interrogate that system using T4/IDS and report
0.		Remove road wheels	50.			findings*  Corrections read test (see IMARNING ever nege)
1.		Inspect brake pads for wear, calipers for leaks and disks for condition	50. 51.		łН	Carry out road test <i>(see WARNING over page)</i> Reset service interval announcement indicator
2.		Replace Brake Fluid (Every 3 years)*	52.		l H	Endorse service record
3.		Renew fuel filter element (Diesel)	53.		iH	Check for any applicable outstanding service actions or recalls
4. 5.		Renew fuel filter element ( <i>Diesel</i> ) - <i>Chinese markets only</i> Drain fuel sedimentor ( <i>Diesel</i> )	54.		i I	Report any unusual features of vehicle condition and additional work required
٥.		Refit road wheels to opposite sides of the same axle (Use anti-sieze				7
6.		compound on spigot bore) Not vehicles fitted with uni-directional tyres				
_		Check operation of door checks, bonnet catch & fuel flap and lubricate door				
1.		checks				
8.		Apply lubricant to door seals - Nordic markets only				
		MAIN SERVICE (UNDER BONNET)				
9.		Check anti-freeze specific gravity				
0.		Renew coolant (Every 10 years)				
1.	105k					
2.		90k Renew spark plugs (V6)				
3.		Renew spark plugs (Vehicles using leaded fuel or low cost spark plugs)				
4.	451	60k Renew air cleaner element ( <b>Petrol</b> )				
25. 26.	45K	90k Renew air cleaner element (Diesel) Clean throttle disc (V8) - Gulf markets only				
.0. 27.	$\vdash$	Check condition of ancillary driving belts	The	maint	nanco	items listed, are those recommended for vehicles operating under normal driving
8.		150k Renew ancillary driving belts (V8)				conditions. More frequent attention may be necessary if the vehicle is subject to
9.	105k	Renew ancillary driving belts (V6)				on, extremes of temperature, dusty conditions, off road driving or frequent towing
0.	105k	Renew ancillary driving belt (Diesel)		ailers.		· · · · · · · · · · · · · · · · · · ·
1.	4051	Renew front and rear camshaft timing helts tensioners and tensioner holt	Serv	rice che	eck con	npleted, cosmetic/corrosion inspection check completed and service portfolio book
1.	105k	(Diesel)		orsed.		
32.		Check/top up brake, PAS and clutch fluid levels and screen washer reservoirs				
3.		Check/top up battery electrolyte level <i>low maintenance battery fitted</i>	Nam	ne:		Signature: Date:

30/1/2009 JLR 11 81 10\_7E

WARNING: Two wheel roller tests must not be carried out. Four wheel roller tests must be limited to 5 km/hour (3 miles/hour).

## **IMPORTANT - OIL CHANGE DIESEL ENGINES**

If the vehicle is operated on fuel with a high sulphur content (over 0.7) the oil change intervals must not exceed 6,000Km (3750 miles)

If the vehicle is operated on fuel with a moderate sulphur content (between 0.3 - 0.7) the oil change intervals must not exceed 12,000Km (7500 miles)

## IT IS RECOMMENDED THAT:

Comments/Remedial Work

After 50 miles continuous use in severe off road conditions - wading, deep mud and abrasive grit/slurry - the electric park brake should be inspected, cleaned and adjusted, and the ancillary drive belt should be inspected and cleaned.

Air suspension vehicles used extensively in arduous/ off road conditions will require the compressor inlet filter to be replaced at more regular intervals.

When the vehicle is used in dusty or field conditions or deep wading, frequent attention to the air cleaner may be required.

When the vehicle is used in areas where fuel quality is poor, more frequent draining of the fuel filter/ sedimentor may be required.

If the vehicle is used with leaded fuel the spark plugs must be replaced every 15,000 miles.

For full details regarding the operations contained in this maintenance check sheet, please refer to the workshop manual.

## GLOSSARY:

**OIL SERVICE** = The oil service is applicable to all vehicles. It is carried out at 6 month or 7,500 mile intervals, whichever occurs first.

MAIN SERVICE = The main service is applicable to all vehicles. It is carried out at 12 month or 15,000 mile intervals, whichever occurs first.

Main Service "A" is applicable at 12 months/15,000 miles, 36 months/45,000 miles, 60 months/75,000 miles 84 months/105,000 miles and so on.

Main Service "B" is applicable at 24 months/30,000 miles, 48 months/60,000 miles, 72 months/90,000 miles, 96 months/120,000 miles and so on. Some items do not need to be carried out at every main service and these items are identified by an indicator in the tick box e.g. 60k (This indicates that this item is only applicable every 60.000 miles)

NOTE: The service required should be at the time or distance stated, which ever occurs first.