Ir./Mrs./Ms.:						Model:						F	Reg. No.:											
nvoice/Job No.:						Odometer Reading:					_ \	V.I.N.:												
Service type:	0	Α	0	В	0	Α	0	В	0	Α	0	В	0	Α	0	В	0	Α	0	В	0	Α	0	В
Months: 000 miles:	3 3.75	6 7.5	9 11 25	12 15	15 18 75	18 22.5	21 26 25	24 30	27 33 75	30 37.5	33 41 25	36 45	39 48 75	42 52.5	45 56 25	48 60	51 63 75	54 67.5	57 71 25	60 75	63 78 25	66 82.5	69 86 25	72 90



## DISCOVERY 3 (ALL MODELS ARDUOUS)

Adjust/Lubricate/Replace - Labour cost included in scheduled time except items marked \*
Check - After the checking procedure, cleaning, adjusting, repairing or replacing is subject to extra labour and material cost

Chec	k - After the c	hecking procedure, cleaning, adjusting, repairing or replacing is subject to extra labour and mate	rial cost.	MAINTENANCE CHECK SHEET
	Oil	OIL SERVICE	MAIN SERVICE (I	
1. 2. 3.		Renew engine oil and filter (Every 3 months / 3,750 miles) Inspect brake pads for wear, calipers for leaks and disks for condition (Every 3 months / 3,750 miles) Inspect road wheel speed sensor harness for damage (Every 3 months / 3,750 miles)	34. Check exterior of i 35. Check/top up batte Check battery con	e, PAS and clutch fluid levels and screen washer reservoirs ntercooler and remove debris using low pressure hose. ery electrolyte level <i>low maintenance battery fitted</i> dition and check/top up battery electrolyte level <i>low tery fitted - MENA markets only</i>
4. 5.		Drain fuel sedimentor ( <i>Diesel</i> ) ( <i>Every 3 months / 3,750 miles</i> ) Adjust the electric park brake shoes ( <i>Every 3 months / 3,750 miles</i> )	A B MAIN SERVICE (U	·
6.		Check the condition of the electric park brake system (Every 3 months / 3,750 miles)	39. 150k Renew automatic	arbox oil <b>(Every 10 years)</b> transmission oil and filter <b>(Every 10 years)</b>
	A B	- /		x oil, replace drain and fill plug washers
7. 8. 9. 10.		Check condition and security of seats and seatbelts Check operation of all lamps, horns and warning indicators Check operation of front/rear wipers and washers and condition of wiper blades Select the LOW range gears and drive the vehicle 3 to 4 vehicle lengths then re select HIGH range gears Replace pollen filter	42. 75k Renew locking diff 43. Check for free play 44. Check condition of 45. Replace all flexible Check visually bra	in all suspension and body mounting rubbers all suspension, driveshafts and steering boots and gaiters brake hoses ( <i>Every 6 years</i> )* ke servo hose, brake, fuel, PAS and clutch pipes, unions esses for chafing, leaks and corrosion
		MAIN SERVICE (VEHICLE EXTERIOR)	48. Check exhaust sys	stem for leaks, security and damage
12. 13. 14. 15. 16. 17. 18. 19. 20. 21.		Annual corrosion/cosmetic inspection - Using annual corrosion inspection sheet Check tyre pressures, condition and tread depth.  Remove road wheels Replace Brake Fluid (Every 2 years)* Renew fuel filter element (Diesel) Refit road wheels to opposite sides of the same axle ( Use anti-sieze compound on spigot bore ) Not vehicles fitted with uni-directional tyres Visually check intercooler/radiator for external obstructions and fan blades for damage Renew the air suspension inlet filter Check operation of door checks, bonnet catch & fuel flap and lubricate door checks Apply lubricant to door seals - Russian and Nordic markets only	50. Check torque of tie Check shock absord damage  52. If fault lamp(s) are findings*  53. Carry out road test 54. Reset service intel 55. Endorse service re 56. Check for any app	I ball joint fixings and condition of ball joints and dust covers a rod end nuts M12 tie rod end nuts only - 76 Nm rbers/height sensors and harness assembly for leakage and illuminated, interrogate that system using T4/IDS and report it (see WARNING over page) roal announcement indicator scord licable outstanding service actions or recalls al features of vehicle condition and additional work required
		MAIN SERVICE (UNDER BONNET)		
22. 23. 24. 25. 26. 27. 28. 29. 30. 31.		Check anti-freeze specific gravity Renew coolant (Every 10 years)* Renew spark plugs (Vehicles using leaded fuel or low cost spark plugs) Renew spark plugs Renew air cleaner element (Petrol) Renew air cleaner element (Diesel) Clean throttle disc (V8 - Gulf markets only) Check condition of ancillary driving belts Renew ancillary driving belts (Petrol) Renew ancillary driving belt (Diesel) Renew front and rear camshaft timing belts, tensioners and tensioner bolt (Diesel)	driving, road and climatic conditions, subject to stop/start operation, extrer frequent towing of trailers. See recom Service check completed, cosmetic/correndorsed.	ose recommended for vehicles operating under arduous. More frequent attention may be necessary if the vehicle is mes of temperature, dusty conditions, off road driving or imendations on back of sheet.  osion inspection check completed and service portfolio book

30/1/2009 JLR 12 05 10\_6E

WARNING: Two wheel roller tests must not be carried out. Four wheel roller tests must be limited to 5 km/hour (3 miles/hour).

## **IMPORTANT - OIL CHANGE DIESEL ENGINES**

If the vehicle is operated on fuel with a high sulphur content (over 0.7) the oil change intervals must not exceed 6,000Km (3750 miles)

If the vehicle is operated on fuel with a moderate sulphur content (between 0.3 - 0.7) the oil change intervals must not exceed 12,000Km (7500 miles)

## IT IS RECOMMENDED THAT:

Comments/Remedial Work

At 144,000 Km (90,000 miles) or every six years, whichever is the sooner, all hydraulic brake fluid hoses should be renewed

After 50 miles continuous use in severe off road conditions - wading, deep mud and abrasive grit/slurry - the electric park brake should be inspected, cleaned and adjusted, and the ancillary drive belt should be inspected and cleaned.

Air suspension vehicles used extensively in arduous/ off road conditions will require the compressor inlet filter to be replaced at more regular intervals.

When the vehicle is used in dusty or field conditions or deep wading, frequent attention to the air cleaner may be required.

When the vehicle is used in areas where fuel quality is poor, more frequent draining of the fuel filter/ sedimentor may be required.

If the vehicle is used with leaded fuel the spark plugs must be replaced every 15.000 miles.

For full details regarding the operations contained in this maintenance check sheet, please refer to the workshop manual.

## GLOSSARY:

OIL SERVICE = The oil service is applicable to all vehicles. It is carried out at 3 month or 3,750 mile intervals, which ever occurs first.

MAIN SERVICE = The main service is applicable to all vehicles. It is carried out at 6 month or 7,500 mile intervals, whichever occurs first.

Main Service "A" is applicable at 6 months/7,500 miles, 18 months/22,500 miles, 30 months/37,500 miles 42 months/52,500 miles and so on.

Main Service "B" is applicable at 12 months/15,000 miles, 24 months/30,000 miles, 36 months/45,000 miles, 48 months/60,000 miles and so on. Some items do not need to be carried out at every main service and these items are identified by an indicator in the tick box e.g. 60k (This indicates that this item is only applicable every 60,000 miles)

NOTE: The service required should be at the time or distance stated, which ever occurs first.