Published: 11-May-2011

Brake System - General Information - Brake System BleedingVehicles With: Standard Brakes


General Procedures

WARNING: If any components upstream of the Hydraulic Control Unit (HCU), including the HCU itself are replaced, the brake system must be bled using the procedure on T4. This will ensure that all air is expelled from the new component(s).

- NOTE: Bleeding of the brake system can be carried out using the procedures given on T4, or by using the procedure below. The following procedure covers bleeding the brake system if components downstream of the HCU have been replaced.
- NOTE: Where only the primary or secondary brake circuits have been disturbed in isolation, it should only be necessary to bleed that circuit. Partial bleeding of the hydraulic system is only permissible if a brake tube or hose has been disconnected with only minimal loss of fluid.
 - 1. WARNING: Do not work on or under a vehicle supported only by a jack. Always support the vehicle on safety stands.

Raise and support the vehicle.

- 2. Check that all the brake line connections are tight and that there are no signs of leaks. If any leak of brake fluid is observed, investigate and rectify the cause of the leak before bleeding the brakes.
- **3.** Pump the brake pedal until the brake vacuum assistance is exhausted.
- 4. Remove the plenum chamber panel.
 - Release the 2 clips.



5. WARNING: Do not allow dirt or foreign liquids to enter the reservoir. Use only new brake fluid of the correct specification from airtight containers. Do not mix brands of brake fluid as they may not be compatible.

CAUTION: Brake fluid will damage paint finished surfaces. If spilled, immediately remove the fluid and clean the area with water.

Remove the brake fluid reservoir cap.

- Disconnect the brake fluid reservoir electrical connector.
- 6. Fill the brake fluid reservoir to the MAX mark.
- 7. Install the bleed tube to the brake caliper bleed screw and immerse the free end of the bleed tube in a bleed jar containing a small quantity of approved brake fluid.