

Service schedule

Customer copy

If fault lamp(s) are illuminated, interrogate that system using the JLR approved diagnostic equipment and report findings.*

SERVICE TYPE:

MODEL:

Replace brake fluid.*

48000 miles / 36 months service

Discovery 4 / L319

V.I.N.:

SALLAAAG5GA837684

Please note that service intervals always represent the maximum time and distance that should exist between servicing. Driving style and conditions may necessitate earlier

servicing as indicated by the notifications on your instrument panel. SERVICE ITEMS Check operation of all lamps, horns and warning indicators. Check operation of Windshield and headlight wipers and washer jets. Select the LOW range gears and drive the vehicle 3 to 4 vehicle lengths then re-select HIGH range gears. Renew pollen filter. Check tyre pressures, condition, tread depth, signs of uneven wear and suitability (including spare). Remove road wheels. Check brake pads for wear, calipers for leaks and discs for condition. Drain fuel filter water trap Refit road wheels (Not vehicles fitted with uni-directional tyres). Check condition of removable towbar Check and top-up clutch and PAS fluid levels and screen washer reservoirs. Check brake fluid level is between Min and Max. Refer to the workshop manual for more information. Using the Jaguar Land Rover approved diagnostic tool, check the DEF level. Top up DEF tank. Renew engine oil and filter. Adjust the electric park brake shoes. Carry out road test. Reset service indicator. Re-set oil level indicator. Endorse service record. Report any unusual features of vehicle condition and additional work required. Labour cost included in scheduled time except items marked *

	L/F	R/F	L/R	R/R	SPARE
Tyre Pressure					
Tyre Tread Depth					
Tyre Condition					